

Specification			
Main Board	CPU	Intel® i5-2510E 2.5 GHz with L3 Cache 3MB	
	Chipset	HM65	
	System Memory	1 x SO-DIMM DDRIII 1333, up to 4GB	
Display	TFT LCD	38.1cm (15")	
	Brightness	250nits	
	Resolution	1024 x 768	
	Touch Screen	True Flat Projected Capacitive Technology / True Flat 5-Wire Resistive	
Storage	HDD Type	1 x SATA 6.4cm (2.5")HDD , SSD (optional)	
I/O Ports -External	DC Input	1 x Mini Din 4P (DC 12V only)	
	Cash Drawer	1 x RJ-11 (Power Pin 12V)	
	Network (LAN)	1 x Gigabit Ethernet by RJ-45	
	USB Port	4 x USB 2.0	
	Serial Port	4 x RS-232 COM1/2 : DB-9, RS-232, Pin9 w/RI/5V/12V Selectable by BIOS COM3/4 : RJ-48 , RS-232, Pin10 w/RI/5V/12V Selectable by BIOS	
	Audio Port	1 x Line-out ; 1 x Mic-In	
	PS/2 Port	1 x PS/2 connector for Keyboard	
	LPT Port	1 x DB-25 Printer Port (Standard)	
I/O Ports -Internal	VGA Port	1 x DB-15 VGA Port (optional)	
	Card Reader & iButton	COM5 : Internal Pin header for Card Reader & iButton	
	Audio	HD Audio, 2W Speaker x 2	
Compliance	Bus Expansion	1 x Mini-PCI-E Slot	
	System Management	IP 66 on front panel	
	OS Support	Desktop Management Interface (DMI)	
		Preboot Execution Environment (PXE)	
Wake on LAN (WoL)			
Advanced Configuration and Power Interface (ACPI)			
Power Supply	External adapter, DC Model:120 Watts, Voltage:+12VDC 10A max.		
Material	Main Unit: Die-casting aluminum ; I/O Cover:Plastic		
Color	Main Unit: Gray / White / Black *Customized color for plastic parts		
Certifications	CE, FCC, Class-B, RoHS, WEEE		
Dimension( W x H x D )	370 x 300 x 236 mm		
Weight	5.96 Kg (Aluminium Base: 1 Kg )		
VESA Mounting	100 x 100 mm		
Operating Temperature	0°C ~ 40°C, 10% ~ 90% RH, non-condensing		
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH, non-condensing		