

SSD2815

28"Resizing LCD,1000 nits LED backlight, 1366x256 ultra wide aspect ratio 16:3

SSD2815 is an innovative ultra-wide, sunlight readable, LED backlight LCD display. it provides LCD panel with specific ratios for digital signage, public transportation, exhibition hall, department store, vending machine and industrial applications. Incorporating with A.D. control board and backlight design, it is high brightness and sunlight readable panel, can display high-quality video with energy-efficient.

Key Features

- Resizing LCDUltra Wide Screen (16 : 3)
- Sunlight Readable
- LED Backlight
- High Brightness 1000 nits
- Low Power Consumption
- High Uniformity (90%)
- Wide Dimming
- Life Expectancy (70,000hrs)
- Slim Bezel



	Specifications	V1
Model No.	SSD2815	
Description	28" Resizing LCD, 1000 nits LED backlight, 1366x256	
Display Area	697.68 x 130.7 mm	
Brightness	1,000 cd/m ²	
Resolution	1366 x 256	
Aspect Ratio	16:3	
Contrast Ratio	2500:1	
Pixel Pitch (mm)	0.51075 x 0.51075	
Viewing Angle	176°(H), 176°(V)	
Display Colors	16.7M	
Response Time (Typical)	6.5 ms	
Sync	LVDS	
Power Consumption	28W	
Dimensions (mm)	740.2 x 167.2 x 56	
Weight (Net)	7.2kg (1/pc packing), 13.5kg (2/pcs packing)	
LED Driving Board	LID28A01	
Control Board (Optional)	AD2662GD / AD2662GDVAR	
□AD2662GD	VGA + DVI	
□AD2662GDVAR	VGA + DVI (Optional AV/ S-Video / Component / Audio)	
Others		
F / R Control Button	5 Key / 4 Key	
□4 Key	Power Switch, Menu, Select (+,-),	
□ 5 Key	Power Switch, Menu, Select (+,-),Auto	
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock	
Optional	Touch Screen	

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.

SSD= Panel+ LED Driving Board + Control Board