

Specification Description		
Display	TFT LCD	38.1cm (15")
	Brightness	250nits
	Resolution	1024 x 768
	Touch Screen	True Flat Projected Capacitive Technology / True Flat 5-Wire Resistive (USB)
I/O Ports	DC Input	1 x DC Jack 5.5mm*2.5mm 2Pin (DC 12V only)
	Audio Input	1 x Audio Jack 3.5mm
	VGA Input	1 x D-SUB 15 Pin
	USB Port	1 x USB Host (USB Host For Touch )
	Serial Port	1 x RS-232 (Optional, for MSR/iButton)
	PS/2 Port	1 x PS/2 Host for MSR & iButton (Optional, for MSR/iButton)
	Audio	AC 97 2.0 compliant, 2W Speaker x 2
Compliance		IP 66 on front panel
Power Supply		External adapter, DC Model:80 Watts, Voltage:+12VDC 6.6A max.
Material		Main Unit: Die-casting aluminum ; I/O Cover:Plastic
Color		Main Unit: Gray / White / Black *Customized color for plastic parts
Certifications		CE, FCC, Class-A, RoHS, WEEE
Dimension( W x H x D )		370 x 300 x 236 mm
Weight		4.4 Kg (Aluminium Base: 1 Kg )
VESA Mounting		100 x 100 mm
Operating Temperature		0°C ~ 40°C, 10% ~ 90% RH, non-condensing
Storage Temperature		-20°C ~ 60°C, 10% ~ 90% RH, non-condensing