

Construction	Heavy-duty steel chassis
CPU / CHIPSET	Intel® Core™ i3-350M Processor (3M Cache, 2.26 GHz) Intel® Core™ i5-450M Processor (3M cache, 2.40 GHz) Intel® Pentium® Processor P6000 (3M Cache, 1.86 GHz) Intel® HM55 chipset
Memory	2x SO-DIMM DDR3 800/1066 up to 8GB
I/O Panel	Front I/O panel 3x 3.5mm Phone Jack, support 5.1 channel audio output 1x eSATA and USB 2.0 combo connector 3x USB 2.0 1x Power LED 1x Storage status LED (HDD/Card reader) 1x Wifi status LED 1x Reset Button 1x Power Button 1x 3 in 1 Card Reader (SD / MMC / MS) Rear I/O panel 1x DC JACK for DC12V single power input 1x DVI-I for DVI-D or VGA output 1x HDMI (V1.3 compatible) 1x RJ-45 GbE port 2x USB 2.0 1x COM Port support RS-232/422/485 (Offer +5V/+12V output selection) 2X Wifi external antenna (optional) 1x 3G external antenna (optional) 1x S/PDIF Output
Storage	1x 2.5" Hard Drive Bay (SATA)
Wireless	1x WLAN mini PCIe card (optional) Or 1x 3G module mini PCIe card (optional)
Power Supply	Input: 100-240 VAC, 50-60 Hz Output: 65W, +12VDC/5.4A output
Expansion Slot	2 x half size mini PCIe slot (Optional for 3G/WiFi module) 1x SIM card slot (for 3G appliance) support user accessible
Cooling	System Fan with smart FAN function
Temperature/ Humidity	Operating: 0°C to 40°C, 0%-90%, non-condensing Storage: -20°C to 80°C, 0%-90%, non-condensing
Dimensions (WxHxD)	200 x 153.3 x 35 mm (WxHxD)
Weight	1 kg
Mounting	Wall-Mount, VESA Mount
Certification	CE, FCC Class A